

WL600 Sonic Water Level Meter

Polluted Well Level Sounder and Depth Measuring Meter



Description

Global Water's WL600 Sonic Water Level Meter is a self-contained, battery operated meter that uses sound waves to measure well water level. Fast, accurate measurements are possible in the field or anywhere, without the use of down-hole probes or instrumentation. The unit is light in weight, compact, versatile and easy to operate.

Operation

Contact Global Water for all your instrumentation needs: Water Level Water Flow Water Samplers Water Quality Weather Remote Monitoring Control The meter is simple to operate. Select either the NORMAL (10-500 feet) or DEEP (200 to 1500 feet) setting on the DEPTH switch. Then to measure a capped well, simply insert the duct into the access port and push the power-on switch. In a few seconds the water level will appear on the digital display. In the NORMAL setting, the sonic sounder stays activated for 5 seconds or 5 pings. Using the DEEP mode the level sounder emits 4 pings in 16 seconds. For more measuring time, hold the switch down as long as necessary.

For uncapped wells, use the provided cover plate. It slips onto the measuring duct and provides a seal for up to 6 inch diameter casings. Cover plates for larger diameters can be easily fabricated from plastic or metal sheet.

- Fast accurate water level measurements in seconds
- Avoid cross contamination
- No equipment to clean
- Works in cased steel or PVC capped wells, partially cased rock wells, crooked wells and wells with pipes, wiring and operating pumps.

Specifications

Performance:

Measurement range: Normal 10-500' or Deep 200-1500' Readout accuracy: <u>+</u> 0.1' Measurment accuracy: <u>+</u> 0.2% of reading* Operating temperature: 30-140° F Power: 8 AA dry cell batteries Dimensions: (excluding sonic measuring duct) Length: 7" Height: 4" Width: 5" Sonic measuring duct diameter: 5/8" Sonic measuring duct length: 2" Weight: 3 1/2 lbs.

* Under certain conditions, accuracy may exceed this limit; when the well casing is discontinuous; when the well casing is highly corroded or rough; when large obstructions e.g. pipe joints or wiring exceed half the area of the well casing; if the well casing is less than 2 inches or greater than 10 inches in diameter

Options and Price List

WL600 Sonic Water Level Meter	\$1393
WL610 Case for Sonic Water Level Meter	\$175



ABASOLO OTE 1087 Int. CENTRO MONTERREY Nuevo León México C.P. 64000 Pagina web: <u>www.instrutechsa.com</u> Correo: <u>ventas@instrutechsa.com</u> Tel.(52) (818) 3402831